MADEIRA Technical Datasheet

Jan 2022

EASY WATER SEAL Art.No. 035ST104

Article Description Waterproof film for embroidery

Composition 100% Polyurethane

Weight in g per m² (\pm 5%) 120g/m²

Make Up Available Roll: 45,50cm x 100m

Main areas of application Used to permanently seal embroidery on waterproof textiles

Features

- Easy water seal is a two-layer adhesive film with an adhesive layer and a barrier layer.
- At long last a heat applicable film perfect for providing a waterproof seal designed to be used on light to medium weight vinyl or polyurethane coated fabrics, ideal for raincoats and waterproof jackets.
- The adhesive force of Easy water seal will be re-activated each time it is ironed.
- Easy water seal can be applied with hot air sealer, but also with heat press or iron.

Application recommendations

Due to the extremely large range of fabrics and finishing, it is essential to run tests concerning operating temperatures and adhesive quality prior to production. Fabrics with special finishing or coating should be ironed or heat-pressed once before application of Easy water seal.

Easy water seal achieves its full adhesive force after 48 hours.

Application suitable by hot air sealer, iron or heat press. If fabric is suitable for heat-press, selection of this method is recommended.

Optimal processing:

- 1. Cut Easy water seal into the size needed, at least with 2 cm overlap around the embroidery.
- 2. Place the shiny side of Easy water seal to the back side of embroidery.
- 3. Press Easy water seal with pre-heated iron or heat press against fabric.

Heat press	Iron

Temperature 120°C 2-3 points depending on fabric, without steam

Pressure 3 bar first bond lightly without pressure, then press as strong as possible

Duration approx. 5-8 sec. min. 30 sec.

Recommendations for care



Easy water seal can be ironed at higher temperatures, dependent upon base materials.

The care instructions are for reference only, due to the delicate waterproof fabric, other cleaning and drying methods should be tested before starting production.

To improve this product Madeira reserves the right to alter the specifications or modify the appearance of products without notice. Information and technical data in this document are guidelines and no warranted characteristics. Small variations due to production process are possible.



Zinkmattenstraße 38 D-79108 Freiburg Tel.: +49 (0) 761 – 51 04 00 E-Mail: service@madeira.de

